

Programme and Proceedings

SWIM 2014

23rd Salt Water Intrusion Meeting



June 16–20, 2014
Husum, Germany

Editors

Helga Wiederhold, Leibniz Institute for Applied Geophysics, LIAG

Johannes Michaelsen, CONSULAQUA

Klaus Hinsby, GEUS

Broder Nommensen, LLUR

Title**SWIM 2014**

23rd Salt Water Intrusion Meeting
Programme and Proceedings

Editors

Helga Wiederhold, Johannes Michaelsen, Klaus Hinsby, Broder Nommensen

Book compilation and formatting

Smart Abstract, Gabriele Köhn und schicker-sign, Regina Schicker

Printing

NEUE PERSPEKTIVEN Digital- und Offsetdruck

1st Edition

June 2014

ISBN 978-3-00-046061-6

Leibniz-Institut für Angewandte Geophysik
Stilleweg 2, 30655 Hannover

Poster Directory

- P-45** Technical Aspects relating to Salt Water Intrusion problems
Hoang Phuc — p. 292
- P-46** Optimisation of subsurface fresh water storage in new land developments
Marianne Tijss — p. 410
- P-47** Calibrating a seawater intrusion model using surrogate simulations
Daan Herckenrath — p. 162
- P-48** Lessons learned from a regional variable density groundwater flow model and implemented climate change scenarios: a Dutch case
Esther van Baaren — p. 416
- P-49** iMOD: A high performance open source framework for SEAWAT
Jarno Verkaik — p. 437
- P-50** eMOD : a MATLAB application for MODFLOW-based groundwater flow and solute transport models
Alexander Vandenbohede — p. 424
- P-51** Recent Updates to the SEAWAT Computer Program
Christian Langevin — p. 219
- P-52** Saltwater intrusion in the Crau coastal aquifer (South of France): validation of variable density modeling using geophysical and geochemical data
Bach Thao Nguyen — p. 261
- P-53** Combining numerical modelling and field-based methods to obtain spatially and temporally variable recharge to a semi-arid coastal aquifer: Uley South Basin, South Australia
Carlos Miraldo Ordens — p. 246
- P-54** In search for clay and salt, combining traditional techniques with airborne geophysics (SkyTEM) to optimize the 3D image of the subsurface
Sander de Haas — p. 79
- P-55** Integrating improved conceptual knowledge into a 3-D variable density numerical model for a heavily exploited coastal aquifer with submarine spring discharge in South Portugal
Rui Hagman (unable to attend the meeting) — p. 185

Saltwater intrusion in the Crau coastal aquifer (South of France): validation of variable density modeling using geophysical and geochemical data

Bach Thao Nguyen, Olivier Banton, Adriano Mayer, Konstantinos Chalikakis and Michel Daniel
Université d'Avignon et des Pays de Vaucluse – UMR 1114 EMMAH, 84000 Avignon, France

ABSTRACT

The research focus on the effect of variable groundwater density on the modeling of seawater intrusion in coastal aquifers. In this setting, the concomitant presence of freshwater and saltwater alters flow patterns typically represented by the Darcy equation. Models of ground water subjects to density changes suffer of several difficulties: 1) The change on the aquifer permeability due to the one of salinity is difficult to take into account during simulation and generates instability. 2) Influences of heterogeneity in this context are more important than in other setting having constant density. 3) Data set must be detailed in order to get a reliable model results. 4) In general, the results of modeling are less robust.

To address and discuss these problems, we set up a variable density groundwater model using FEFLOW. The studied area is the Crau aquifer, in the Mediterranean region of Southern France. It has been chosen because of the long term records of hydrogeological and climatic data (salinity, piezometric levels, water geochemistry, rainfall, irrigation seepages and exploitation).

The first results indicate that the interface between freshwater and saltwater is very influenced by the heterogeneities in aquifer properties and the effects of irrigation and groundwater withdrawal. To better constraint the data set for the variable-density flow model, geophysical acquisitions have been carried out using Electrical Resistivity Tomography (ERT) and Electromagnetic surveys (EM). This has provided subsurface information on vertical salinity and lithology distribution. Furthermore, Radon-222 activity in groundwater has been used to estimate independently the groundwater velocity following the method of Schubert et al 2011. Radon-based groundwater velocity results of the same order of magnitude as the velocity estimated with FEFLOW. Groundwater discharges into ponds surrounding the Crau area, will also be assessed during the course of this study by using Radon mass balance between ponds and groundwater, as well as salinity data.

Keywords: saltwater intrusion, Crau aquifer, FEFLOW, EM-34, ERT, Radon-222