

FECON

Listen to the Earth, Conquer the Height



**TECHNICAL
WORLD**



YAMAGUCHI
UNIVERSITY



**PROCEEDINGS OF THE 4th INTERNATIONAL CONFERENCE
VIETGEO 2018, QUANG BINH, 21-22 SEPTEMBER, 2018**

**GEOLOGICAL AND GEOTECHNICAL
ENGINEERING IN RESPONSE TO CLIMATE CHANGE
AND SUSTAINABLE DEVELOPMENT OF INFRASTRUCTURE**



SCIENCE AND TECHNICS PUBLISHING HOUSE



**PROCEEDINGS OF THE 4th INTERNATIONAL
CONFERENCE VIETGEO 2018**

**GEOLOGICAL AND GEOTECHNICAL
ENGINEERING IN RESPONSE TO CLIMATE
CHANGE AND SUSTAINABLE
DEVELOPMENT OF INFRASTRUCTURE**

Quang Binh, 21&22 September 2018

INTERNATIONAL CONFERENCE VIETGEO 2018

ORGANIZING COMMITTEE:

| | |
|--------------------------------|---|
| Assoc. Prof. Ta Duc Thinh | VAEGE, Vietnam |
| Assoc. Prof. Le Hai An | HUMG, Vietnam |
| Dr. Nguyen Duc Ly | Quang Binh Depart. of Science and Technology |
| Prof. Motoyuki Suzuki | Yamaguchi University, Japan |
| Assoc. Prof. Nguyen Huy Phuong | VAEGE, Vietnam |
| Assoc. Prof. Do Minh Duc | VAEGE, Vietnam |
| Prof. Nguyen Quoc Dung | Hydraulic Construction Institute, Vietnam |
| Prof. Suksun Horpibulsuk | Suranaree University of Technology, Thailand |
| Mr. Le Cao Minh | Technical World Co. Ltd, Vietnam |
| Assoc. Prof. Nguyen Van Vuong | VNU University of Science, Vietnam |
| Prof. Ding Wenqi | Tongji University, China |
| Assoc. Prof. Dau Van Ngo | Ho Chi Minh University of Technology, Vietnam |
| Assoc. Prof. Do Quang Thien | Hue University of Science, Vietnam |
| Assoc. Prof. Nguyen Quang Minh | HUMG, Vietnam |

SCIENTIFIC COMMITTEE:

| | |
|---------------------------------|--|
| Prof. Tran Thanh Hai | HUMG, Vietnam |
| Prof. Motoyuki Suzuki | Yamaguchi University, Japan |
| Prof. Emeritus. Hiroshi Matsuda | Yamaguchi University, Japan |
| Prof. Suksun Horpibulsuk | Suranaree University of Technology, Thailand |
| Prof. Pham Van Ty | VAEGE, Vietnam |
| Prof. Nguyen Quoc Dung | Hydraulic Construction Institute, Vietnam |
| Prof. Faquan Wu | General Secretary of IAEG |
| Prof. Ding Wenqi | Tongji University, China |
| Dr. Kochi Yoshifumi | K's Lab - Geotechnical Consultant, Japan |
| Assoc. Prof. Tran Manh Lieu | VNU University of Science, Vietnam |

CONFERENCE SECRETARIAT:

| | |
|-------------------------|----------------|
| Dr. Bui Truong Son | HUMG, Vietnam |
| Dr. Bui Trong Vinh | HCMUT, Vietnam |
| Dr. Nguyen Chau Lan | UTC, Vietnam |
| Dr. Vu Ba Thao | HyCI, Vietnam |
| Dr. Tran Thanh Nhan | HUSC, Vietnam |
| Dr. Nguyen Van Phong | HUMG, Vietnam |
| Dr. Nguyen Thi Nu | HUMG, Vietnam |
| Dr. Nhu Viet Ha | HUMG, Vietnam |
| Msc. Nguyen Thanh Duong | HUMG, Vietnam |
| Msc. Duong Van Binh | HUMG, Vietnam |
| Msc. Nguyen Van Hung | HUMG, Vietnam |
| Msc. Vu Thai Linh | HUMG, Vietnam |
| Msc. Pham Thi Ngoc Ha | HUMG, Vietnam |
| Msc. Phung Huu Hai | HUMG, Vietnam |

**PROCEEDINGS OF THE 4th INTERNATIONAL
CONFERENCE VIETGEO 2018**

**QUANG BINH, VIETNAM
21&22 September 2018**

**GEOLOGICAL AND GEOTECHNICAL
ENGINEERING IN RESPONSE TO CLIMATE
CHANGE AND SUSTAINABLE
DEVELOPMENT OF INFRASTRUCTURE**

Editors:

**TA DUC THINH
PHAM VAN TY
NGUYEN HUY PHUONG
DO MINH DUC
BUI TRUONG SON
TRAN MANH LIEU
VU BA THAO**

SCIENCE AND TECHNICS PUBLISHING HOUSE

INTERNATIONAL CONFERENCE

VIETGEO 2018

**GEOLOGICAL AND GEOTECHNICAL ENGINEERING
IN RESPONSE TO CLIMATE CHANGE AND
SUSTAINABLE DEVELOPMENT OF INFRASTRUCTURE**

21&22 September 2018

QUANG BINH, VIETNAM

Organized by

Vietnam Association of Engineering Geology and the Environment (VAEGE)
Hanoi University of Mining and Geology (HUMG)
Quang Binh Department of Science and Technology
Technical World Co. Ltd (TW)
FECON Corporation
Yamaguchi University, Japan
Suranaree University of Technology, Thailand
Tongji University, China
Ho Chi Minh University of Technology (HCMUT)
Hue University of Sciences - Hue University (HUSC)
VNU University of Science, Vietnam National University, Hanoi (VNU-HUS)
Hydraulic Construction Institute (HyCI)

With the supports of

Quang Binh Department of Science and Technology
Technical World Co. Ltd (TW)
FECON Corporation
GMC Investment and Development Co. Ltd.
Research Center for Technology and Industrial Equipment, HCMUT
Union of Survey and Construction J.S.C (USCO)
Geotechnical Research Centre, HUMG
Nam Mien Trung Co. Ltd.
Hanoi Construction Design Investigation Consultants J.S.C
Power Engineering Consulting J.S.C 1 (PECC1)
Hydraulic Construction Institute (HyCI)

TABLE OF CONTENT

| | |
|----------------------|---|
| Preface | x |
|----------------------|---|

SESSION 1 GEOLOGICAL AND GEOTECHNICAL ENGINEERING IN RESPONSE TO CLIMATE CHANGE

| | |
|---|----|
| Assessing the resilience of Bac Bo Plain, Vietnam under the impacts of climate change: case study in Hai Dong commune <i>Do Minh Duc, Duong Thi Toan, Tran Thi Luu</i> | 3 |
| Impacts of global climate change, sea level rise and economic-contruction activity to the sustainable development of the Quang Ninh coastal area <i>Le Trong Thang</i> | 14 |
| Bioengineering approach for shoreline protection using geosynthetics: A malaysian experience <i>L.K.Lim, Y.J.Fong</i> | 23 |
| Properties of soft soil ground in the Quang Ninh coastal area and proposal of soft soil improvement in the context of the climate change and sea level rise <i>Nguyen Thi Nu, Nguyen Van Phong, Do Minh Toan, Nguyen Viet Tinh, Pham Thi Ngoc Ha</i> | 32 |
| Erosion and accretion at the estuaries of Quang Binh province in the period of 2000 to 2016 <i>Do Quang Thien, Ho Trung Thanh, Nguyen Quang Tuan, La Duong Hai, Le Thi Cat Tuong, Tran Thi Ngoc Quynh</i> | 38 |
| Effects of climate change on slope stabilization in the Cao Son coal waste area, Cam Pha, Quang Ninh <i>To Xuan Vu, Nguyen Van Hung, To Hoang Nam</i> | 52 |
| Effects of fine particles and water content on shear strength and riverbank stability: A case study in the Red riverbank in Hanoi area <i>Duong Thi Toan, Ngo Hong Hue</i> | 62 |
| Evaluation of adaptive capacity to salinity intrusion of the Da Nang city in the context of climate change <i>Nguyen Ngoc Truc, Nguyen Thi Oanh, Ho Xuan Huong</i> | 71 |
| Effects of capillary water on groundwater in coastal sand dunes in the North Central Region of Vietnam <i>Nguyen Thanh Cong, Nguyen Huy Vuong, Pham Tuan, Tran Van Quang, Vu Ba Thao, Bui Truong Son</i> | 79 |
| The neotectonic and active tectonic influence on coastal erosion at Quang Nam province of Vietnam <i>Hoang Ngo Tu Do, Do Quang Thien, Tran Thanh Hai, Le Thanh Phong</i> | 84 |
| Impacts of climate change on the Upper - Middle Pleistocene aquifer in the Ca Mau peninsula and adaptive solutions <i>Dao Hong Hai, Nguyen Viet Ky, Bui Tran Vuong</i> | 89 |

SESSION 2
**GEOTECHNICS FOR SUSTAINABLE DEVELOPMENT
 OF INFRASTRUCTURE**

| | |
|--|-----|
| Physical scale model of horizontal water collecting system for weirs in the Northwest Vietnam <i>Nguyen Huy Vuong, Nguyen Chi Thanh, Pham Tuan, Tran Van Quang, Le Vu Minh, Vu Ba Thao, Bui Truong Son</i> | 101 |
| Settlement of saturated clay layer subjected to cyclic loading with a wide range of loading periods <i>Hiroshi Matsuda, Tran Thanh Nhan, Hiroyuki Hara</i> | 110 |
| A case study on the determination of the excavated trench depth in unsaturated soil constructed by open trench method without supporting structures <i>Nguyen Xuan Man, Le Van Hung, Kenneydy Chibuzor ONYELOWE</i> | 121 |
| A method of evaluation of wave loads acting on vertical pier with non-prismatic section in the deep sea <i>Dang Xuan Truong, Dau Van Ngo, Le Van Nam</i> | 130 |
| Classifying the foundation structure for sustainable planning and development of Hanoi urban center <i>Tran Manh Lieu, Nguyen Huy Phuong, Duong Thi Toan, Tran Thi Luu, Nguyen Van Vu, Nguyen Van Thuong, Nguyen Ngoc Truc</i> | 135 |
| Establishing geology engineering map of the Hai Thinh area for planning of eco-social sustainable development <i>To Hoang Nam, To Xuan Vu</i> | 142 |
| Application of acoustic waves for assessment of excavation damaged zone for underground construction in rock mass <i>Hoang Dinh Phuc, Chu Viet Thuc</i> | 149 |
| Calculating the large two-way batter bearing pile foundation for pillar supported dam <i>Tran Van Thai, Nguyen Dinh Truong</i> | 160 |
| Influence of embankment height and soil parameters on piled embankments by 3D numerical simulation <i>Pham Van Hung, Vu Minh Ngan</i> | 172 |
| Application of transformation theory of engineering geological properties of soils to determine the distribution of Hai Hung formation in the Hanoi area <i>Ta Duc Thinh</i> | 180 |
| Analysis of metal pollution in groundwater of Pleistocene aquifer in Ho Chi Minh city, Vietnam <i>Tran Thi Phi Oanh, Nguyen Viet Ky, Dau Van Ngo, Ho Chi Thong, Mai Hoang Phuc , Nguyen Thi Ngoc Thuy</i> | 184 |
| Evaluation of the operating capacity of ports based on the analysis of hydrodynamics and the erosion - accretion regulation of the coastal areas in the North Vietnam <i>Nguyen Huy Phuong, Duong Van Binh, Nguyen Huy Quang</i> | 195 |
| Characteristics of cyclic deformation phases of soils distributed in the urban area of Hanoi for seismic design <i>Nguyen Van Phong</i> | 201 |
| The sand-cement-lime column method for soil improvement: A case study in Tay Thai Thuy High school, Thai Binh province <i>Ta Duc Thinh, Nguyen Duc Ly</i> | 207 |

| | |
|---|-----|
| Effects of lime on improving swelling characteristics of the soil weathered from acidic magmatic rock in Central Highlands of Vietnam <i>Nguyen Huy Vuong, Vu Ba Thao, Dang Hoang Thanh, Nguyen Manh Ha, Bui Truong Son, Pham Tuan, Dinh Van Thuc, Tran Van Quang</i> | 215 |
| Soil improvement through biological-based method <i>Pham Phu Vinh, Leon A. van Paassen</i> | 225 |
| Residual shear strength of soil and its shear displacement rate dependency: an overview <i>Motoyuki Suzuki, Nguyen Thanh Duong</i> | 233 |
| Application of Roclab software in defining the mechanical characteristics of contact rock in dam foundation for small-scale hydroelectric projects: A Case study in the Long Tao hydroelectric project, Dien Bien province <i>Bui Truong Son, Vu Thai Linh</i> | 246 |
| Consolidation properties of some Holocene soft clayey soils in the Quang Nam - Da Nang coastal plain <i>Nguyen Thi Ngoc Yen, Nguyen Hoang Giang, Do Quang Thien</i> | 253 |
| Effects of cycle number of triaxial cyclic test and sand density on dynamic properties of sand of the Thai Binh formation in Hanoi area <i>Nguyen Van Hung, Nguyen Thanh Duong, Bui Van Binh, Phung Huu Hai, Pham Thi Ngoc Ha</i> | 263 |
| Effects of soft ground structure on the Hau riverbank failure process in An Giang province, Vietnam <i>Tran Le The Dien, Huynh Trung Tin, Trang Nguyen Dang Khoa, Bui Trong Vinh, Ta Duc Thinh</i> | 268 |
| Effects of undrained cyclic shear and Atterberg's limits on the secondary consolidation of soft soils <i>Tran Thanh Nhan, Hiroshi Matsuda, Hoang Thi Sinh Huong, Hidemasa Sato, Do Quang Thien, Duong Phuoc Huy, Nguyen Van Thien, Lai Phuoc Thanh Hoai, Vo Thanh Men, Tran Thi Anh Dai, Nhu Viet Ha</i> | 278 |
| Downhole seismic testing to determine elastic parameters of the ground for anti - seismic designs: A case study in the industrial zone Vung Ro, Phu Yen <i>Bui Truong Son, Vu Thai Linh</i> | 287 |
| Evaluation of sand-cement column solution for soft soil improvement in the North Coastal Highway, Vietnam <i>Nguyen Thi Dieu, Ta Duc Thinh, Nguyen Duc Manh</i> | 294 |
| Study, analysis and assess effectiveness of soft soil improvement using PVD combine vacuum preloading at hyosung vina chemicals project at Ba Ria Vung Tau province, Vietnam <i>Phan Thanh Tien, Nguyen Tan Son</i> | 303 |

SESSION 3

GEOTECHNICAL MONITORING AND MATERIALS

| | |
|---|-----|
| Assesment of capability of using natural puzzolan in Dak Nong, Viet Nam for soil stabilization <i>Vu Ba Thao, Nguyen Huu Nam, Pham Van Minh, Tran Van Quan, Nguyen Huy Vuong, Dinh Van Thuc</i> | 312 |
| Comparison of numerical modeling and field monitoring of deep foundation of high-rise building: A case study of Summit Building, Tran Duy Hung, Hanoi, Vietnam <i>Bui Truong Son, Duong Van Binh, Nguyen Thi Trang</i> | 320 |
| Scientific basis for setting up a monitoring system for geo-environmental disaster prevention and sustainable development of the Red River dynamic zone in Hanoi <i>Nguyen Cong Kien</i> | 329 |

| | |
|---|-----|
| Using coal bottom ash of An Khanh thermal power plant as aggregate replacement of concrete <i>Nguyen Thi Nu, Bui Truong Son</i> | 338 |
| Propose new approach method to determine scale module for granular soils in serve of natural building materials Application for Granular Soils in Quang Tri -Thua Thien Hue Coastal Plain) <i>Do Quang Thien, Dang Quoc Tien, Ho Trung Thanh, Le Thi Cat Tuong, Tran Thi Ngoc Quynh</i> | 342 |
| Effect of particle size distribution of Liem Son, Kim Bang, Ha Nam limestone grading as inert additive on But Son cement Motar <i>Ta Thi Toan, Nguyen Thi Nu, Vu Thi Ngoc Minh</i> | 350 |
| The Basic characteristics and applicability of granulated blast furnace slag (GBFS) as building materials in Vietnam <i>Nguyen Ngoc Truc, Nguyen Van Vu, Nguyen Thi Oanh</i> | 357 |
| Reusability the bottom ash from coal thermal power plant (CTPP) for graded materials and concrete aggregate based on particle size distribution <i>Nguyen Thi Nu, Nguyen Ngoc Dung, Nhu Viet Ha, Duong Van Binh, Phan Tu Huong, Ta Thi Toan</i> | 365 |
| Exploring the potential of high-accuracy landslide detection and monitoring based on new remote sensing data and techniques <i>Nhu Viet Ha</i> | 373 |

SESSION 4 GEOHAZARDS AND SLOPE STABILITY

| | |
|---|-----|
| Remedy of a collapsed riverbank protection structure in Thailand <i>Suksun Horpibulsuk, Artit Udcomchai, Menglim Hoy, Arul Arulrajah</i> | 387 |
| Analysis the causes of land subsidence in Ca Mau city <i>Dao Hong Hai, Nguyen Viet Ky, Tra Thanh Sang</i> | 396 |
| Using logistic regression and neural networks for landslide susceptibility assessment along the transport arteries in the mountainous areas of Quang Nam province <i>Do Minh Duc, Nguyen Khac Hoang Giang , Dao Minh Duc , Do Minh Ngoc, Dinh Thi Quynh, Dang Thi Thuy, Nguyen Huu Ha, Nguyen Van Binh, Hoang Hai Yen , Do Van Vung</i> | 403 |
| Probabilistic Monte Carlo simulation for assessment the slope instability due to rainfall on the Nha Trang - Da Lat route <i>Nguyen Thanh Danh, Dau Van Ngo, Ta Quoc Dung, Nguyen Huu Son</i> | 412 |
| Factors triggering landslides in timor-leste <i>Benjamim Hopffer Martins, Motoyuki Suzuki, Eguchi Tsuyoshi, Noppawan Tamkuan, Masahiko Nagai</i> | 421 |
| Landslide hazard and prevention in the Ward 2, Dalat city, Vietnam <i>Nguyen Viet Ky, Bui Trong Vinh, Kanno Takami</i> | 431 |
| Safety assessment of a creeping landslide based on field measurements <i>Nguyen Tai Son, Pham Van Ty, Le Quang Huy</i> | 438 |
| Rainfall-induced shallow landslides: Behavior and mitigation approach <i>Avirut Chinkulkijniwat, Somjai Yubochit</i> | 445 |
| Assessment, classification and solutions for landslide mitigation along the National Highway No. 6 <i>Tran Manh Lieu, Duong Thi Toan, Tran Thi Luu, Nguyen Ngoc Truc</i> | 461 |

| | |
|---|-----|
| Examining the reliability of the logarithmic sliding surface method in slope stability analysis <i>Pham Huu Sy, Pham Phu Vinh, Le Vu Minh</i> | 472 |
| Application of artificial neural networks for landslide forecasting models in the mountainous areas of Xin Man district, Ha Giang province <i>Pham Quoc Khanh, Nguyen Thi Kim Thanh</i> | 477 |
| Causes of landslide in the Ong Tuong hill area, Hoa Binh city and treatment solutions <i>Duong Van Binh, Bui Truong Son, Pham Thi Ngoc Ha, Nguyen Minh Hien</i> | 484 |
| Probabilistic analysis of rainfall-induced landslides in Quang Nam province <i>Nguyen Khac Hoang Giang, Trinh Quoc Anh, Dang Thi Thuy, Do Minh Ngoc, Dao Minh Duc, Hoang Hai Yen, Nguyen Huu Ha, Do Minh Duc</i> | 492 |
| Analysis of pore water pressure and slope displacement by historical rain series in Xin Man district, Ha Giang province, Vietnam <i>Dao Minh Duc, Tran Quoc Cuong, Do Minh Duc, Dang Thi Thuy</i> | 499 |
| Characteristics of geotechnical and environmental hazards in Hanoi area <i>Nguyen Van Vu, Nguyen Van Thuong, Nguyen Ngoc Truc</i> | 510 |
| Analysis of sediment distribution and transport trends at the Da Dien estuary, Central Vietnam <i>Dinh Thi Quynh, Do Minh Duc, Nguyen Tien Giang, Tran Ngoc Anh</i> | 517 |
| Slopes in loose rock - stabilisation and erosion protection in a single operation <i>Tran Dong, DENNIS Gross</i> | 524 |

SESSION 5 TECHNICAL NOTES

| | |
|--|-----|
| Distribution and engineering properties of clayey soils of the Phu Bai formation in Thua Thien Hue and Quang Tri <i>Hoang Thi Sinh Huong, Tran Thanh Nhan, Pham Huu Tuyen, Do Quang Thien, Ho Sy Thai, Massimo Sarti</i> | 533 |
| Soft soil improvement with cement and fly ash in Vietnam <i>Chu Long Hai, Nguyen Chau Lan, Hoang Duc Chi, Nguyen Vinh, Nhu Tuan</i> | 542 |
| Soft soil improvement in the 2/9 Road (extension) project, Vinh Long town, Vinh Long province <i>Thai Ba Ngoc, Tran Van Xuan, Hoang Quang Trung Phi, Luong Bao Minh, Truong Xuan Hien, Vo The Anh</i> | 552 |
| Introduction to structure of the water filter solutions in boat pumping station for aquacultural water supply in the Ca Mau peninsula <i>Nguyen Quoc Dung, Phan Dinh Tuan, Le Anh Duc, Nguyen Quang Thanh</i> | 564 |
| Effects of hydraulic conductivity on the riverbank stability <i>Duong Thi Toan</i> | 570 |
| Discussion on nearly correct determination of shear strength of strongly weathered rock zone Ia2 <i>Bui Khoi Hung, Dang Hoang Cam, Ho Minh Long, Tran Xuan Sinh</i> | 579 |
| Using piezcone penetration testing of soils (CPTU) to determine the physico-mechanical properties of sand using for sea dykes in Tra Vinh coast, South Vietnam <i>Nguyen Huu Son, Dau Van Ngo, Ho Chi Thong, Nguyen Thi Ngoc Thuy</i> | 584 |

COMPARISON OF NUMERICAL MODELING AND FIELD MONITORING OF DEEP FOUNDATION OF HIGH-RISE BUILDING

Bui Truong Son¹, Duong Van Binh¹, Nguyen Thi Trang²

¹ Hanoi University of Mining and Geology, Vietnam

² ADCOM Civil engineering Consultancy & Investment JSC, Vietnam

Corresponding author' Email: buitruongson@humg.edu.vn

Abstract: In the trend of urban development in Vietnam, the construction of high-rise buildings is indispensable. Due to the limited construction area, these works often have to develop underground space, also known as basement (deep foundation). In fact, the construction of deep foundations have occurred many incidents. There are many causes leading to incidents, including causes of errors in the geotechnical investigation, resulting in not enough data on the physical-mechanical properties of rock and soil. Therefore, the simulation of the actual working condition of the ground around the foundation is not accurate. This paper analyzes the effect of geotechnical survey results on the calculation of the deep foundation in a particular project and compares it with the actual observation results.

Keywords: deep foundation; Mohr-Coulomb model; inclinometer.

1. Introduction

In the trend of urban development in Vietnam, the construction of high-rise buildings is indispensable. Due to the limited construction area, these works often have to develop underground space, also known as basement (deep foundation). There are some typical projects in Ha Noi such as: Pacific Place, 83 Ly Thuong Kiet, Royal City Building, Mo Shopping Center, Lotte Center Hanoi with 5 basements, Tan Hoang Minh D'.Palais de Louis with 4 basements ... In fact, the construction of deep foundations have occurred many incidents, such as: The construction of the basement of Pacific Building, Nguyen Thi Minh Khai Street in 2007 has collapsed the building of the Southern Institute of Social Sciences; Construction of the basement of Saigon Residences building in 2007 has tilt Cosaco apartment building, 5 Nguyen Sieu, ... There are many causes leading to incidents, including causes of errors in the geotechnical investigation, resulting in not enough data on the physical-mechanical properties of rock and soil. Therefore, the simulation of the actual working condition of the ground around the foundation is

not accurate. Therefore, it is necessary to improve the quality of geotechnical investigation to reduce the difference in the results of design calculations and actual construction.

2. Geotechnical conditions of construction site

2.1. Location

Summit Building is located at 216 Tran Duy Hung, Trung Hoa, Cau Giay, Hanoi. The project is easily connected with the roads such as Nguyen Chanh, Ring Road 3, Lang Road ... and easily move to neighboring districts such as Dong Da District, Thanh Xuan District, Tu Liem District, Fig 1.

- Opposite the Grand Plaza;
- Located 100 meters from Big C supermarket;
- Located 120 meters from the D'Capitale Project;
- Located 200 meters from Thang Long Boulevard;
- Located 300 meters from Amsterdam High School;
- Located 3 kilometers from Royal City.




Fig. 1. Location of Summit Building

1.2. Geotechnical conditions of construction site

Based on the results of geotechnical investigation, stratigraphy of the construction site. It is classified into 06 layers and 01 sub-layers, shown on the engineering geological section of the project, Fig 2. Describe layers from top to bottom as follows:

Layer 1: Filled soil: Sand, clay mix

Layer 2: Clay, sandy clay, brownish gray, firm;

Layer 3: Very fine sand, brownish gray, medium dense;

Layer 4: Sandy clay, brownish gray, content organic, stiff;

Layer 5: Very fine sand, brownish gray, dense;

Sub-Layer 5a: Sandy clay, brownish gray, stiff;

Layer 6: Gravel, content coarse sand, very dense.

1.3. Retaining structure

The building uses barretle walls made of reinforced concrete, 28m long. Retaining wall are assembled with prefabricated panels, 80 cm thick, average width of 5 meters, using reinforced $\varnothing 25$. The wall is also used to make basement wall of high-rise building, Fig 3.

2. Evaluating the horizontal displacement of the retaining wall of Summit building by Inclinometer.




Fig. 2. Engineering geological section of construction site




Fig. 3. Cross section of retaining wall

The building needs to observe the horizontal displacement of the retaining wall during the excavation and construction of the underground part of the building.

Measure the horizontal displacement of the retaining wall with Inclinator: 04 points and observation from top to bottom of observation tube, the distance between measurement points is 0.5m.

Installation depth: Inclinator is installed at 29.0 meters depth at 04 positions and 35 meters at 01 position, Fig 4. The actual depth after installation is as follows, Table 1.

Tab. 1. Installation depth and peak height of the monitoring tube

| Position | IN-01 | IN-02 | IN-03 | IN-04 | IN-05 |
|-----------------------------|-------|-------|-------|-------|-------|
| Installation depth, (meter) | 29 | 29.5 | 35 | 29 | 29 |




Fig. 4. Location of horizontal displacement monitoring points




Fig. 5. Movement chart at position IN-01, IN-02




Fig. 6. Movement chart at position IN-03, IN-04




Fig. 7. Movement chart at position IN-05

After 24 observation cycles of nearly 6 months (from 15/8/2017 to 01/02/2018), the horizontal displacement of the retaining wall (Fig 5,6,7) is as follows:

- Position IN-01, the largest displacement in A direction is 21.40mm at depth 19.0m.
- Position IN-02, the largest displacement in A direction is 18.20mm at depth 19.0m.
- Position IN-03, the largest displacement in A direction is 25.17mm at depth 18.0m.
- Position IN-04, the largest displacement in A direction is 9.30mm at depth 18.0m.

- Position IN-05, the largest displacement in A direction is 15.30mm at depth 19.0m.

The results of the observation reflected the movement of the retaining walls in both space and time:

- By space: the most displacement at depths from 14.0 meter to 24.0 meter (9.93mm). The smallest displacement is from the top of the wall to 6.0 meter (0mm).
- By the time: The displacement of the wall increases and stabilizes, the displacement is small.
- The observation results clearly reflect the changing law of the retaining wall.

- The level of variation is within the allowable limit (horizontal displacement allowed is $H/500$, with H is the depth of the retaining wall (TCVN 9381: 2012, item 5.2.5.4).

- The retaining wall system of deep foundation is completely stable, ensuring the durability of the building and safety during construction.

3. Evaluating the horizontal displacement of the retaining wall of the Summit building using the Plaxis 2D

3.1. Construction sequence, Fig 8

Construction method: Top - Down method

Construction phases (ground level is 0m):

- Phase 1: Construction of retaining wall.

- Phase 2: Lowering the groundwater level to -5.4m, excavate to the elevation -4.4m, then executing the floor B0 at 0.0m

- Phase 3: Lowering the groundwater level to -7.9m, excavate to the elevation -6.9m, then executing the floor B1 at -4.9m.

- Phase 4: Lowering the groundwater level to -10m, excavate to elevation -9.5m, then executing floor B2 at -7.5m

- Phase 5: Lowering the groundwater level to -13m, excavation to elevation -12.7m. Then executing B3 floor at -10.7m

- Phase 6: Lowering the groundwater level to -17m, excavate to elevation -16.7m, then executing B4 at -12.7m and B5 at -14.7m.




Fig. 8. Retaining wall and excavation phases.

3.2. Input parameters of the model, Table 2,3,4

Due to inadequate geotechnical survey data, we used the Mohr - Coulomb model to calculate the deep excavation for this case. This model has the advantage of being simple, just the basic physical-mechanical characteristics of the land to calculate. However, this model does not accurately simulate the work of soil and structures.

In the deep foundation, the soils works in σ_3 reduction condition. So, in order to simulate the ground conditions, the parameters must be obtained from the triaxial compression test (σ_3 reduction). However, for this work, only the results from the uniaxial compression test, so the parameters used to run the model will reduce the accuracy of the results.

Based on previous studies, we propose modifying the elastic modulus values in the model to verify the results of the calculation with the actual observation results.

According to Nguyen Truong Huy, (2015). E_{ref} was obtained according to the results of the 3-axis compression test (σ_3 reduction); or $E_{ref} = (3 \div 5) E_{oed}$.

So, the problem is realized with two modulus values of the ground plane:

- Case 1: $E_{ref} = E_{oed}$
- Case 2: $E_{ref} = 5E_{oed}$

Tab. 2. Input parameters of soil layer ($E_{ref} = E_{oed}$)

| Layer | 1 | 2 | 3 | 4 | 5 |
|---------------------------------------|---------|-----------|---------|-----------|---------|
| | MC | MC | MC | MC | MC |
| | drained | undrained | drained | undrained | drained |
| Thickness (m) | 2.85 | 5.3 | 5.4 | 18.4 | 10.5 |
| γ_{unsat} (kN/m ³) | 18 | 18.37 | 13.25 | 18.55 | 13.18 |
| γ_{sat} (kN/m ³) | 18.5 | 18.63 | 15.24 | 18.90 | 15.29 |
| C (kN/m ²) | 10 | 12 | 0 | 11 | 0 |
| $\varphi^{(o)}$ | 30 | 11.17 | 19.35 | 14.28 | 29.18 |
| $\psi^{(o)}$ | 0 | 0 | 0 | 0 | 0 |
| E_{ref} (kN/m ²) | 42500 | 6270 | 27500 | 7770 | 5700 |
| ν | 0.3 | 0.31 | 0.3 | 0.32 | 0.3 |
| R_{inter} | 0.9 | 0.7 | 0.9 | 0.7 | 0.9 |

Tab. 3. Input parameters of soil layer ($E_{ref} = 5.E_{oed}$)

| Layer | 1 | 2 | 3 | 4 | 5 |
|---------------------------------------|---------------|-----------------|---------------|-----------------|---------------|
| | MC drained | MC undrained | MC drained | MC undrained | MC drained |
| Thickness (m) | 2.85 | 5.3 | 5.4 | 18.4 | 10.5 |
| γ_{unsat} (kN/m ³) | 18 | 18.37 | 13.25 | 18.55 | 13.18 |
| γ_{sat} (kN/m ³) | 18.5 | 18.63 | 15.24 | 18.90 | 15.29 |
| C (kN/m ²) | 10 | 12 | 0 | 11 | 0 |
| $\varphi^{(o)}$ | 30 | 11.17 | 19.35 | 14.28 | 29.18 |
| $\psi^{(o)}$ | 0 | 0 | 0 | 0 | 0 |
| E_{ref} (kN/m ²) | 42500 | 31350 | 27500 | 38850 | 5700 |
| ν | 0.3 | 0.31 | 0.3 | 0.32 | 0.3 |
| R_{inter} | 0.9 | 0.7 | 0.9 | 0.7 | 0.9 |

Tab. 4. Input parameters of retaining wall

| Element | Properties | Symbol | Index | Unit |
|-----------------------------------|-------------------|--------|--------------------|------|
| Retaining wall d=800mm M500 | Normal stiffness | 80%EA | 2.3×10^6 | kN |
| | Flexural rigidity | 80%EI | 1.23×10^5 | kN/m |
| | Poisson index | ν | 0.15 | |

Tab. 5. Input parameters of reinforced concrete floor

| Element | Properties | Symbol | Index | Unit |
|--|----------------------|--------|--------------------|------|
| Reinforced concrete floor d=0.3m M500 | Compression rigidity | 80%EA | 8.64×10^5 | kN |
| | Flexural rigidity | 80%EI | 6.48×10^3 | kN/m |

The results obtained in each phase are as follows, Fig 9-13.




Fig. 9. The displacement of the wall and the soil after phase 2




Fig. 10. The displacement of the wall and the soil after phase 3




Fig. 11. The displacement of the wall and the soil after phase 4




Fig. 12. The displacement of the wall and the soil after phase 5




Fig. 13. The displacement of the wall and the soil after phase 6

Tab. 6. Comparison of the largest horizontal displacements from MC model and observation ($E_{ref} = E_{oed}$)

| Phase | Mohr-Coulomb (mm) | Inclinometer (mm) | Difference (%) |
|-------|---------------------|-------------------|----------------|
| 2 | 42.48 | 16.00 | 62.33 |
| 3 | 64.24 | 17.86 | 74.51 |
| 4 | Soil body collapses | 17.80 | |
| 5 | Soil body collapses | 18.50 | |
| 6 | Soil body collapses | 25.17 | |

Tab. 7. Comparison of the largest horizontal displacements from MC model and observation ($E_{ref} = 5E_{oed}$)

| Phase | Mohr-Coulomb (mm) | Inclinometer (mm) | Difference (%) |
|-------|-------------------|-------------------|----------------|
| 2 | 12.80 | 16.00 | -25 |
| 3 | 18.15 | 17.86 | 1.6 |
| 4 | 23.74 | 17.80 | 25 |
| 5 | 29.56 | 18.50 | 37.4 |
| 6 | 40.85 | 25.17 | 38.38 |




Fig. 14. Horizontal displacements in Phase 2 (Case 1)




Fig. 15. Horizontal displacements in Phase 2 (Case 2)




Fig. 16. Horizontal displacements in Phase 3 (Case 1)




Fig. 19. Horizontal displacements in Phase 5 (Case 2)




Fig. 17. Horizontal displacements in Phase 3 (Case 2)




Fig. 20. Horizontal displacements in Phase 6 (Case 2)




Fig. 18. Horizontal displacements in Phase 4 (Case 2)

Analytical results (Table 6,7; Fig 14-20) show that when changing the E_{ref} value will change the behavior of the soils in the foundation.

The $E_{ref} = E_{oed}$ value incorrectly simulates the displacement of the soil in the foundation pit, leading to the ground being damaged in Phase 4. This is not consistent with the observation results, foundation and retaining walls are stable.

The shape of the deformation graph is also significantly different from the deformation graph of the Inclinometer. When using the $E_{ref} = 5.E_{oed}$, the displacement of the soil in the foundation is more consistent with the actual observation. However, the difference in deformation increased with the depth of the foundation, the shape of the graph is not really consistent with the results of the observation.

The analysis has demonstrated the influence of the results of the survey to the results of design calculations

4. Conclusion

The analysis results show that the horizontal displacement in the Mohr-Coulomb model is much larger than the Inclinator observation (average 20 ÷ 40%) and the difference increases with depth. There are differences in horizontal displacement graphs in the two methods. This difference is due to:

- The retaining wall of Plaxis was retained, while the Inclinator was installed deeper than the wall and fixed, so that the foot of the retaining wall was not displaced as the Mohr-Coulomb model.

- The parameters of the MC model are taken from simple laboratory experiments that do not accurately reflect the actual behavior of the ground.

- MC model is the model of elastic behavior, not showing the process of unloading - reloading of soil during construction.

- The most important parameter for the deep foundation calculation is the E_{ref} obtained from a uniaxial compression test with a constant value of effective stress during the loading process.

Nomenclature

The following symbols are used in this paper

c = cohesion, kN/m²

E_{ref} = Young's modulus, kN/m²

MC = Mohr-Coulomb

γ_{sat} = saturated unit weight of material, kN/m³

γ_{unsat} = unsaturated unit weight of material, kN/m³

φ = friction angle, °

ψ = angle of dilation, °

ν = Poisson's ratio

References

- [1] Displacement observation report of the retaining wall of Summit building, 216 Tran Duy Hung Street, Cau Giay District, Hanoi (2017).
- [2] Tran Ngoc Dong (2014). Research on geodetic observation, analysis of foundation deformation and basement of high-rise buildings in the construction phase, PhD thesis. Hanoi.
- [3] Nguyen Minh Tam (2014). Studying the method of calculating suitable soil pressure for retaining wall of foundation. Journal of Construction Science. Hanoi.
- [4] Duong Van Binh (2014). Study to select soil model and material parameters to design solutions for stabilization of deep foundation with Plaxis software". Fundamental research project, Hanoi University of Mining and Geology. Hanoi.
- [5] Nguyen Truong Huy (2015). Study of geotechnical conditions for design and construction of deep foundations, PhD thesis. Hanoi.